

Multi-purpose, anti-ligature and corrosion-resistant luminaires

Robust and durable luminaires with a polycarbonate cover. Extruded aluminium body with die-cast ends. Long life silicone sponge gasket ensuring IP66 rating. Cover secured using tamper-resistant pin Torx screws.

- Robust and durable extruded aluminium body dissipates heat, ensuring long control gear life in higher ambient temperatures
- High impact-resistant, flame-retardant polycarbonate cover
- Cover secured using tamper-resistant T25 pin Torx screws
- Removable gear tray, hangs on safety straps for easy maintenance
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit



IP66

IK10

Up to 172 LL/CW

Specification

Mounting	Surface	IP rating	IP66
Impact rating	IK10	Nominal size	1200 mm 1500 mm
Max presence detection height	4 m		

Lighting

Optic	Clear cover	Lumen output	3,030 lm - 8,145 lm
Efficacy	Up to 172 LL/CW		

Emergency data

Emergency lumen output	560 lm - 630 lm	Emergency type	Maintained
Emergency duration	3 hours	Battery specification	Nickel Metal Hydride (NiMH)

Power

LED power	16 W - 44 W	Circuit power	21 W - 55 W
-----------	-------------	---------------	-------------


LED characteristics

CRI	80+	Colour temperature	4000 K
Rated life (hours)	100 K - L70/B10		

Compliance

UKCA	Yes	CE	Yes
Energy efficiency class	This product contains a light source of energy efficiency class B		

Dimensions



Click or scan here
View A-Line AL variants using
our online filtering tool



Information is correct as of 29 Dec 2024, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.